

PRODUCT

DATA SHEET



Bending
Cutting
Welding
Marking

2024-2025

HIGHTECH INDUSTRY GROUP

BUILD . TO LEAD .

HTPRO


CHANNEL LETTER BENDING MACHINE



High Automation & Efficiency
Fully automated feeding, slotting, bending, and cutting, completing channel letter returns and outside bends with one click, saving time and labor.

Precision & Material Compatibility
Ensures accurate bends matching CNC-cut faces and backs; works with stainless steel, aluminum, and profile materials.

Cost & Energy Savings
Replaces 10–20 manual workers, lowers labor costs, and features an energy-efficient design for cost-effective production.



SOFTWARE

DEVELOPED IN-HOUSE FOR CONTINUOUS IMPROVEMENT.

MULTI-POINT GROOVING, CONTOUR OFFSET, GLUE WEIGHT & AREA CALCULATION, TOOL RADIUS COMPENSATION, MATERIAL MEMORY, AND ONE-CLICK MATERIAL CHANGE.

DESIGNED FOR EFFICIENCY AND PRECISION.

DRIVER

HIGH-POWER SERVO SYSTEM CONTROL WITH HIGH PRECISION, FAST SPEED, AND STRONG TORQUE, IMPROVING LETTERING EFFICIENCY.

FEATURES PROPRIETARY SOFTWARE AND DRIVERS FOR ABSOLUTE CONTROL OVER FEEDING, CUTTING, AND BENDING.



PARTS



MOTORS

THE HT PRO BENDING MACHINE'S MOTOR PROVIDES CONSISTENT, STRONG POWER FOR FEEDING, CUTTING, AND BENDING, ENSURING SMOOTH OPERATION UNDER HEAVY WORKLOADS AND IMPROVING PRODUCTIVITY.

THE MOTOR WORKS WITH THE CNC SYSTEM FOR ACCURATE BENDING AND FEEDING, DELIVERING PRECISE RESULTS WHILE REDUCING ENERGY USE AND LOWERING OPERATING COSTS.

BENDING SYSTEM

FEATURES A PATENTED DUAL-SYSTEM ARC BENDING UNIT, WITH SEPARATE SYSTEMS OPTIMIZED FOR STAINLESS STEEL AND ALUMINUM.

THE LIFTING AND ADD-ON EXTRUSION BENDING MECHANISMS CAN BE SWITCHED ACCORDING TO THE MATERIAL, ENABLING TRUE MULTI-MATERIAL PROCESSING WITH GREATLY IMPROVED EFFICIENCY.



PARTS



FEEDING SYSTEM

INDEPENDENT FEEDING RACK WITH HIGHER LOAD CAPACITY, EQUIPPED WITH A MATERIAL LEVELING DEVICE FOR SMOOTHER AND MORE STABLE FEEDING.

DUAL-ROW ROLLER FEEDING WITH REINFORCED ROLLERS, OFFERING FASTER SPEED AND BETTER STABILITY; ENCODER-CONTROLLED ACCURACY UP TO ≤ 0.1 MM.

SOFTWARE-CONTROLLED UNLOADING SYSTEM PREVENTS SLIPPING AND DEFORMATION, ENSURING HIGH PRECISION.

STEEL CUTTER

STAINLESS STEEL CUTTING SYSTEM
IMPORTED CARBIDE PLANER BLADE WITH AUTOMATIC TOOL ALIGNMENT, REINFORCED 2.5 MM LEAD SCREW, AND SERVO DRIVE FOR FAST, STABLE, AND PRECISE CUTTING.





ALUMINUM CUTTER

75MM BLADE DIAMETER WITH 10 CUTTING HEADS, 2.0 SQUARE GUIDE RAIL FOR ENHANCED STABILITY DURING OPERATION

AUTO-ANGLE RECOGNITION WITH FRONT/BACK OSCILLATING MOTION, MOTORIZED HEIGHT ADJUSTMENT, AND AUTOMATIC DEPTH CONTROL VIA SOFTWARE

REINFORCED 4-COLUMN STRUCTURE FOR STEADY, HIGH-QUALITY CUTS

OIL-WATER SEPARATOR

THE OIL-WATER SEPARATOR EFFECTIVELY REMOVES MOISTURE AND OIL FROM COMPRESSED AIR, ENSURING A CLEAN AND STABLE AIR SUPPLY FOR THE BENDING MACHINE.

THIS HELPS PROTECT PNEUMATIC COMPONENTS, REDUCES WEAR AND CORROSION, AND IMPROVES OVERALL MACHINE RELIABILITY AND SERVICE LIFE.



PARTS



ENCODER

THE ENCODERS FEATURE A DURABLE MECHANICAL STRUCTURE DESIGNED. HIGH-RESOLUTION OPTIONS WITH STABLE PULSE OUTPUT AND STRONG ANTI-INTERFERENCE CAPABILITY.

THEY PROVIDE PRECISE SPEED, POSITION, AND DIRECTION FEEDBACK, SUITABLE FOR SERVO SYSTEMS.

THEY SUPPORT MULTIPLE VOLTAGE LEVELS AND OUTPUT SIGNALS (SUCH AS TTL, HTL, AND LINE DRIVER)

Technical Parameters


Slotting System	Milling cutter & Planner knife
Bending System	Double rod linkage bending method& Double alternate blade
Feeding System	Rolling feeding device
Working Voltage	Single Phase AC 220V,50/60Hz
Cutting Depth Calibration	Automatic by software
Size Accuracy	±0.1mm
Material Height	30~160mm
Material Thickness	0.3 ~1.5mm
Minimum Bending Radius	R≥5mm (AL) , R≥3.5mm (SS)
Input File Format	*.AI
Packing Size	166*80*177cm (2.4m³)
Packing Weight	580KG
Applicable material	Galvanized plate/Iron/ Flat aluminum / Letterume coil/Fold edge aluminum/ Extrusion aluminum profile



LETTERUME (LET-R-EDGE STYLE COIL)



CHANNEL LETTER WITH SPONGE AND PVC
AVAILABLE PROCESSING SIZES: 5CM/7CM/9CM/11CM

APPLICABLE MATERIAL



FLAT ALUMINUM COILS

AVAILABLE PROCESSING SIZES: 3CM UP TO 16CM



SINGLE EDGE COILS

AVAILABLE PROCESSING SIZES: 6CM UP TO 12CM

APPLICABLE MATERIAL



TRIMLESS PROFILE

AVAILABLE PROCESSING SIZES: 5/8/10 CM



GALVANIZED STRIPS

AVAILABLE PROCESSING SIZES: 3CM UP TO 16CM

APPLICABLE MATERIAL



STAINLESS STEEL

AVAILABLE PROCESSING SIZES: 3CM UP TO 16CM

ABOUT US

BUILD . TO LEAD .



Based in Weifang, Shandong, our modern manufacturing base covers over 12,000 m² and integrates research, development, production, and testing in one facility – ensuring stability, efficiency, and quality at every stage.

Hightech provides professional installation, training, and lifetime technical support. Our responsive service team and spare-parts centers ensure fast solutions and long-term reliability for every customer.



Equipped with advanced CNC machining centers, laser cutting systems, precision welding equipment, and intelligent assembly lines, Hightech continuously upgrades its technology to meet global industrial standards.



Driven by passion and professionalism, our international team of engineers, designers, and sales specialists works together to deliver innovative machines and trusted partnerships worldwide under the Hightech brand.





CONTACT US



 USA, Hightech Industry INC USA

 Canada, Hightech Industry Canada


 United Kingdom, Hightech Signage Solutions LTD

 Mexico, Hightech Industry operated by Imprime iya

 Iran, Hightech Industry operated by Aluone

 Brazil, Hightech Industry operated by Banner Jet

 India, Mehta Hightech Industries L.L.P

 IRAQ, BAGHDAD, Hightech Industry operated by AL Sabagh

 Dubai, Hightech Blue LLC

 Indonesia, Hightech operated by PT Digital Prima Imaging



 NO. 6188 WEICHANG ROAD, WEICHENG DISTRICT, WEIFANG CITY, SHANDONG PROVINCE, CHINA

 INFO@HTINDUSTRYCO.COM



WWW.HTINDUSTRYCO.COM



+86 156 2166 0575 / +86 156 2166 0576